

# 

Model VHMD15

NSF. UL CUL LISTED

### SPECIFICATIONS:

Vulcan VHMD15 Humidified Holding Cabinet; Electronic controlled Heating and Holding with an On-Demand Humidity System. Thermostat ranges from 80° F- 200° F. Electronic Humidistat provides humidity to chamber at selected level. Can be used in Holding or Proofing. Chamber capacity is 15 each 18" x 26" sheet pans or 30 each 12" x 20" x 2.5" hotel pans. Exterior and interior is constructed of 20 gauge non-corrosive stainless steel. Welded tubular steel interior frame. Fully insulated. 120v, 1200 w, 10 amp service 5" heavy duty casters (2 swivel with brakes, 2 rigid). Heavy duty Magnetic latch.

Classified by UL to NSF std. #4

UL Listed. UL Listed to Canadian Safety standards.

Item #

C.S.I. Section 11420

## MODEL VHMD15 HUMIDI-HEAT HUMIDIFIED HOLDING SYSTEM

HUMIDI-HEAT HUMIDIFIED HOLDING SYSTEM

### STANDARD FEATURES:


- Electronic Heating controls 80°F 200° holding temperature range
- On-Demand Computer-chip controlled Humidity Levels
- Built-in Humidity System with self contained 1 gallon water reservoir
- Capacity of 15-each 18" x 26" sheet or 30-each 12" x 20" x 2.5" hotel pans
- Heavy duty polished non-corrosive series stainless steel construction 20 gauge exterior and interior
- Welded tubular steel frame
- Fully insulated, 2" in top, 1" in sides and bottom
- Heavy duty 5" casters
- Universal Tray Slides
- 120 Volt 1200 Watt 10 Amp
- Recessed Handles
- Dutch Doors
- Top mount cord and wrap
- Heavy duty positive seal door latching system
- Left or right hand hinging (no charge)

### **OPTIONS:**

- □ 208/240 volt
- □ Transport Package
- □ Full Perimeter Bumper
- □ 6" heavy duty casters
- □ Glass Door (Dutch Doors)
- □ Security package



# MODEL VHMD15 HUMIDI-HEAT HUMIDIFIED HOLDING SYSTEM



**FRONT VIEW** 

SIDE VIEW

Model No.	18 x 26 Capacity	12x20x2.5 Capacity	High	Deep	Wide	Shipping Weight	Volts	Watts	Amps
VHMD15	15	30	65" 1702mm	34¼" 857mm	251⁄8" 724mm	370# 167 kg	120	1200	10

**NOTE:** In line with its policy to continually improve its products, Vulcan-Hart Company reserves the right to change materials and specifications without notice.

VULCAN-HART COMPANY, P.O. BOX 696, LOUISVILLE, KY 40201, TEL. 1-800-814-2028 502-778-2791 QUOTE & ORDER FAX: 1-800-444-0602